

**VALTTI PUUÖLJY (Wood Oil)**

Date 4.6.2008

Previous date: 25.11.2004

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

- 1.1 Identification of the article**
- 1.1.1 Commercial Product Name**  
VALTTI PUUÖLJY (Wood Oil)
- 1.1.2 Product code**  
257 -series
- 1.2 Use of the Substance/Preparation**
- 1.2.1 Intended use**  
Painting work.  
Description: Traditional wood oil
- 1.3 Identification of the company**
- 1.3.1 Supplier**  
Tikkurila Oy
- 1.3.2 Contact information:**
- P.O.Box** P.O.Box 53  
**Postcode and post office** FI-01301 VANTAA  
FINLAND
- Telephone** +358 9 857 71  
**Telefax** +358 9 8577 6936
- 1.3.4 Responsible for the Safety Data Sheet:**  
Tikkurila Oy, Product Safety, e-mail: productsafety@tikkurila.com
- 1.4 Emergency telephone number**
- 1.4.1 Telephone number, name and address**  
Tikkurila Oy, Environment and Safety: +358 9 857 71

**2. HAZARDS IDENTIFICATION**

Flammable.

Harmful, Xn

Harmful by inhalation. Harmful: may cause lung damage if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information on hazard labelling in section 15.1.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

3.1	Hazardous components		3.1.2 Chemical name of the substance	3.1.3 Concentration	3.1.4 Classification
	3.1.1 CAS number	EINECS			
	64742-48-9	265-150-3	Naphtha, hydrotreated heavy (aliphatic hydrocarbon solvent)	50 - 75 %	Xn; R10-65-66
	64742-95-6	265-199-0	Solvent naphtha, light aromatic	10 - 20 %	Xn, N; R10-37-65-66-67-51/53
	68551-44-0	271-378-4	Zinc carboxylate	1 - 2,5 %	Xi, N; R38-50/53
	731-27-1	211-986-9	Tolyfluanid	< 0,5 %	T+, N; R26-36/37/38-43-48/23-50
	96-29-7	202-496-6	Ethyl methyl ketoxime	< 0,5 %	Xn; R21-40-41-43
	55406-53-6	259-627-5	3-Iodo-2-propynyl butyl carbamate	< 0,5 %	Xn, N; R20/22-41-50

**VALTTI PUUÖLJY (Wood Oil)**

Date 4.6.2008

Previous date: 25.11.2004

**4. FIRST AID MEASURES**

- 4.1 Additional advice**  
In all cases of doubt, or when symptoms persist, seek medical attention.
- 4.2 Inhalation**  
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**  
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.
- 4.4 Eye contact**  
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- 4.5 Ingestion**  
If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

**5. FIRE-FIGHTING MEASURES**

- 5.1 Suitable extinguishing media**  
Use foam, CO<sub>2</sub>, powder or water spray.
- 5.2 Extinguishing media which must not be used for safety reasons**  
Waterjet
- 5.3 Specific hazards**  
Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

**6. ACCIDENTAL RELEASE MEASURES**

- 6.1 Personal precautions**  
Avoid breathing vapours. Exclude sources of ignition.
- 6.2 Environmental precautions**  
Do not allow to enter drains or water courses.
- 6.3 Methods for cleaning up**  
Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents. Note! Products containing oxidative drying oil or alkyd (linseed oil varnish, alkyd paints and -lacquers) have a possibility of auto-ignition in porous materials damped by the product. This kind of waste must be collected and stored e.g. in water before disposal or incinerated immediately.

**7. HANDLING AND STORAGE**

- 7.1 Handling**  
Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.
- 7.2 Storage**  
Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- 8.2 Exposure controls**
- 8.2.1 Occupational exposure controls**  
Provide adequate ventilation. Comply with the health and safety at work laws.
- 8.2.1.1 Respiratory protection**

**VALTTI PUUÖLJY (Wood Oil)**

Date 4.6.2008

Previous date: 25.11.2004

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.

**8.2.1.2 Hand protection**

Always wear protective gloves (e.g. nitrile rubber). Barrier creams may also help to protect the exposed areas of the skin.

**8.2.1.3 Eye protection**

Use safety eyewear designed to protect against splashes of liquids.

**8.2.1.4 Skin and body protection**

Use suitable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES****9.1 General Information (appearance, odour)**

Coloured, viscous liquid, strong odour.

**9.2 Important Health Safety and Environmental Information**

**9.2.2 Boiling point/range** 145 - 200 °C \*)

**9.2.3 Flash point** + 36 °C \*)

**9.2.5 Explosive properties**

**9.2.5.1 Lower explosion limit** 0,6 vol-% \*)

**9.2.5.2 Upper explosion limit** 7,0 vol-% \*)

**9.2.7 Vapour pressure** 0,2 kPa (20 °C) \*)

**9.2.8 Relative density** 0,9

**9.2.9 Solubility**

**9.2.9.1 Water solubility** Insoluble

**9.3 Other data**

Evaporation rate (BuAc=1) : 0,14 \*)

\*) = Naphtha, hydrotreated heavy

**10. STABILITY AND REACTIVITY****10.1 Conditions to avoid**

Solvent vapours may form explosive mixtures with air.

**10.2 Materials to avoid**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.3 Hazardous decomposition products**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**11. TOXICOLOGICAL INFORMATION****11.2 Primary irritation**

See section 11.5.

**11.3 Sensitisation**

Contains ethyl methyl ketoxime and tolylfluaniid. May produce an allergic reaction.

**11.5 Human experience**

**VALTTI PUUÖLJY (Wood Oil)**

Date 4.6.2008

Previous date: 25.11.2004

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally. The product contains solvent naphtha, which may cause lung damage if swallowed.

**12. ECOLOGICAL INFORMATION****12.1 Ecotoxicity****12.1.1 Aquatic toxicity**

Solvent naphtha, light aromatic: LC50 = 1-10 mg/l, fish, crustacean, algae (estimate); toxic

**12.3 Persistence and degradability****12.3.1 Biodegradation**

Solvent naphtha, light aromatic: 78 %, 28 d; readily biodegradable

**12.4 Bioaccumulative potential**

Solvent naphtha, light aromatic: octanol/water partition coefficient log Pow = 3,7-4,5 (estimate)

**12.6 Other adverse effects**

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

**13. DISPOSAL CONSIDERATIONS**

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

Risk of self-ignition! Cleaning cloths or sanding dust containing the product can create fire by self-ignition and should therefore be stored in water before disposal, or dried outdoors or incinerated immediately.

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

**14. TRANSPORT INFORMATION**

<b>14.1</b>	<b>UN No</b>	1263
<b>14.2</b>	<b>Packing group</b>	III
<b>14.3</b>	<b>Land transport</b>	
<b>14.3.1</b>	<b>ADR/RID Class</b>	3
<b>14.3.3</b>	<b>Description of the goods</b>	paint
<b>14.4</b>	<b>Sea transport</b>	
<b>14.4.1</b>	<b>IMDG Class</b>	3
<b>14.4.2</b>	<b>Proper shipping name</b>	paint
<b>14.4.3</b>	<b>Further Information</b>	EmS: F-E,S-E
<b>14.5</b>	<b>Air transport</b>	
<b>14.5.1</b>	<b>ICAO/IATA Class</b>	3
<b>14.5.2</b>	<b>Proper shipping name</b>	paint

**15. REGULATORY INFORMATION****15.1 Information on the warning label****15.1.1 Letter code of the warning symbol and indications of danger for the preparation**

Xn Harmful

**VALTTI PUUÖLJY (Wood Oil)**

Date 4.6.2008

Previous date: 25.11.2004

**15.1.2 Names of the ingredients given on the warning label**

Naphtha, hydrotreated heavy (aliphatic hydrocarbon solvent)  
Solvent naphtha, light aromatic  
Tolyfluanid

**15.1.3 R-phrases**

R10 Flammable.  
R20 Harmful by inhalation.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.

**15.1.4 S-phrases**

S2 Keep out of the reach of children.  
S23 Do not breathe vapour/spray.  
S29 Do not empty into drains.  
S51 Use only in well-ventilated areas.  
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**15.1.5 Special regulations on certain preparations**

Contains ethyl methyl ketoxime and tolyfluanid. May produce an allergic reaction.

**16. OTHER INFORMATION****16.1 Full text of R-phrases referred to under sections 2 and 3**

R38 Irritating to skin.  
R26 Very toxic by inhalation.  
R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.  
R10 Flammable.  
R20 Harmful by inhalation.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R20/22 Harmful by inhalation and if swallowed.  
R21 Harmful in contact with skin.  
R65 Harmful: may cause lung damage if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R37 Irritating to respiratory system.  
R40 Limited evidence of a carcinogenic effect.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitization by skin contact.  
R50 Very toxic to aquatic organisms.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

**16.4 Additional information**

The classification of tolyfluanid (in 2.1.4) is based on the proposal of 31. ATP of Directive 67/548/EEC. The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oy, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

**Signature**

a/akk