

**NOVIPUR PRIMER HS**

Date 13.5.2008

Previous date: -

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

- 1.1 Identification of the article**  
**1.1.1 Commercial Product Name**  
 NOVIPUR PRIMER HS
- 1.1.2 Product code**  
 007 1585
- 1.2 Use of the Substance/Preparation**  
**1.2.1 Intended use**  
 Painting work.  
 Description: 2-component polyurethane primer, base part.
- 1.3 Identification of the company**  
**1.3.1 Supplier**  
 Tikkurila Oyj
- 1.3.2 Contact information:**  
**P.O.Box** P.O.Box 53  
**Postcode and post office** FI-01301 VANTAA  
 FINLAND  
**Telephone** +358 9 857 71  
**Telefax** +358 9 8577 6936
- 1.3.4 Responsible for the Safety Data Sheet:**  
 Tikkurila Oy, Product Safety, e-mail: productsafety@tikkurila.com
- 1.4 Emergency telephone number**  
**1.4.1 Telephone number, name and address**  
 Tikkurila Oy, Environment and Safety: +358 9 857 71

**2. HAZARDS IDENTIFICATION**

Highly flammable, F  
 Harmful, Xn  
 Harmful by inhalation and in contact with skin. Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child.  
 Information on hazard labelling in section 15.1.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

| 3.1 | Hazardous components |           | 3.1.2<br>Chemical name of the substance | 3.1.3<br>Concentration | 3.1.4<br>Classification            |
|-----|----------------------|-----------|---|------------------------|------------------------------------|
|     | 3.1.1<br>CAS number  | EINECS    |   |                        |                                    |
|     | 1330-20-7            | 215-535-7 | Xylene                                  | 10 - 20 %              | Xn; R10-20/21-38                   |
|     | 108-88-3             | 203-625-9 | Toluene                                 | 10 - 22 %              | F, Xn; R11-38-48/20-63-65-67       |
|     | 108-94-1             | 203-631-1 | Cyclohexanone                           | 1 - 5 %                | Xn; R10-20                         |
|     | 110-19-0             | 203-745-1 | Isobutylacetate                         | 1 - 5 %                | F; R11-66                          |
|     | 123-42-2             | 204-626-7 | Diacetone alcohol                       | 1 - 5 %                | Xi; R36                            |
|     | 100-41-4             | 202-849-4 | Ethylbenzene                            | 1 - 5 %                | F, Xn; R11-20                      |
|     | 141-78-6             | 205-500-4 | Ethyl acetate                           | 1 - 5 %                | F, Xi; R11-36-66-67                |
|     | 77-58-7              | 201-039-8 | Dibutyltin dilaurate                    | < 0,25 %               | Xn, N; R20/21/22-36/38-48/22-50/53 |

**4. FIRST AID MEASURES**

- 4.1 Additional advice**  
 In all cases of doubt, or when symptoms persist, seek medical attention.

**NOVIPUR PRIMER HS**

Date 13.5.2008

Previous date: -

- 4.2 Inhalation**  
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**  
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.
- 4.4 Eye contact**  
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- 4.5 Ingestion**  
If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

**5. FIRE-FIGHTING MEASURES**

- 5.1 Suitable extinguishing media**  
Use foam, CO<sub>2</sub>, powder or water spray.
- 5.2 Extinguishing media which must not be used for safety reasons**  
Waterjet
- 5.3 Specific hazards**  
Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

**6. ACCIDENTAL RELEASE MEASURES**

- 6.1 Personal precautions**  
Avoid breathing vapours. Exclude sources of ignition.
- 6.2 Environmental precautions**  
Do not allow to enter drains or water courses.
- 6.3 Methods for cleaning up**  
Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

**7. HANDLING AND STORAGE**

- 7.1 Handling**  
Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.
- 7.2 Storage**  
Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- 8.1 Exposure Limit Values**
- 8.1.1 Occupational exposure limit values**
- |                   |               |
|-------------------|---------------|
| Xylene            | 100 ppm (8 h) |
| Toluene           | 20 ppm (8 h)  |
| Cyclohexanone     | 20 ppm (8 h)  |
| Isobutylacetate   | 150 ppm (8 h) |
| Diacetone alcohol | 50 ppm (8 h)  |
| Ethylbenzene      | 100 ppm (8 h) |
| Ethyl acetate     | 400 ppm (8 h) |
- 8.1.2 Information on limit values**  
TLV-TWA = Threshold Limit Values - Time-weighted average / ACGIH 2007
- 8.2 Exposure controls**
- 8.2.1 Occupational exposure controls**  
Provide adequate ventilation. Comply with the health and safety at work laws.

**NOVIPUR PRIMER HS**

Date 13.5.2008

Previous date: -

**8.2.1.1 Respiratory protection**

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.

**8.2.1.2 Hand protection**

Always wear protective gloves (e.g. nitrile rubber). Barrier creams may also help to protect the exposed areas of the skin.

**8.2.1.3 Eye protection**

Safety eyewear must be used, specially during spray-application.

**8.2.1.4 Skin and body protection**

Protective clothing must be used during spray-application.

**9. PHYSICAL AND CHEMICAL PROPERTIES****9.1 General Information (appearance, odour)**

Coloured, viscous liquid, strong odour.

**9.2 Important Health Safety and Environmental Information**

**9.2.2 Boiling point/range** + 111 °C \*)

**9.2.3 Flash point** + 4 °C

**9.2.5 Explosive properties**

**9.2.5.1 Lower explosion limit** 1,2 vol-% \*)

**9.2.5.2 Upper explosion limit** 7,1 vol-% \*)

**9.2.7 Vapour pressure** 2,9 kPa (20 °C) \*)

**9.2.8 Relative density** 1,4

**9.2.9 Solubility**

**9.2.9.1 Water solubility** Insoluble

**9.2.11 Viscosity** flow time more than 30 sec / ISO 3 mm cup

**9.3 Other data**

Evaporation rate (BuAc=1) : 2,3 \*)

\*) = Toluene

**10. STABILITY AND REACTIVITY****10.1 Conditions to avoid**

Solvent vapours may form explosive mixtures with air.

**10.2 Materials to avoid**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.3 Hazardous decomposition products**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**11. TOXICOLOGICAL INFORMATION****11.1 Acute toxicity**

See section 11.5.

**11.2 Primary irritation**

See section 11.5.

**11.3 Sensitisation**

---

**11.5 Human experience**

**NOVIPUR PRIMER HS**

Date 13.5.2008

Previous date: -

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally. The product contains toluene. Possible risk of harm to the unborn child.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**12. ECOLOGICAL INFORMATION****12.6 Other adverse effects**

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

**13. DISPOSAL CONSIDERATIONS**

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

**14. TRANSPORT INFORMATION**

|        |                          |              |
|--------|--------------------------|--------------|
| 14.1   | UN No                    | 1263         |
| 14.2   | Packing group            | II           |
| 14.3   | Land transport           |              |
| 14.3.1 | ADR/RID Class            | 3            |
| 14.3.3 | Description of the goods | paint        |
| 14.4   | Sea transport            |              |
| 14.4.1 | IMDG Class               | 3            |
| 14.4.2 | Proper shipping name     | paint        |
| 14.4.3 | Further Information      | EmS: F-E,S-E |
| 14.5   | Air transport            |              |
| 14.5.1 | ICAO/IATA Class          | 3            |
| 14.5.2 | Proper shipping name     | paint        |

**15. REGULATORY INFORMATION****15.1 Information on the warning label****15.1.1 Letter code of the warning symbol and indications of danger for the preparation**

F Highly flammable  
Xn Harmful

**15.1.2 Names of the ingredients given on the warning label**

Xylene  
Toluene

**15.1.3 R-phrases**

R11 Highly flammable.  
R20/21 Harmful by inhalation and in contact with skin.  
R38 Irritating to skin.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R63 Possible risk of harm to the unborn child.

**15.1.4 S-phrases**

**NOVIPUR PRIMER HS**

Date 13.5.2008

Previous date: -

|        |   |
|--------|---|
| S16    | Keep away from sources of ignition - No smoking.                          |
| S23    | Do not breathe vapour/spray.  |
| S29    | Do not empty into drains.   |
| S33    | Take precautionary measures against static discharges.                    |
| S36/37 | Wear suitable protective clothing and gloves.                             |
| S38    | In case of insufficient ventilation, wear suitable respiratory equipment. |

**16. OTHER INFORMATION****16.1 Full text of R-phrases referred to under sections 2 and 3**

|           |  |
|-----------|--|
| R20/21/22 | Harmful by inhalation, in contact with skin and if swallowed.                                    |
| R36/38    | Irritating to eyes and skin.   |
| R48/22    | Harmful: danger of serious damage to health by prolonged exposure if swallowed.                  |
| R50/53    | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R11       | Highly flammable.  |
| R20/21    | Harmful by inhalation and in contact with skin.  |
| R38       | Irritating to skin.  |
| R48/20    | Harmful: danger of serious damage to health by prolonged exposure through inhalation.            |
| R63       | Possible risk of harm to the unborn child.   |
| R10       | Flammable.   |
| R20       | Harmful by inhalation.   |
| R36       | Irritating to eyes.  |
| R65       | Harmful: may cause lung damage if swallowed.   |
| R66       | Repeated exposure may cause skin dryness or cracking.  |
| R67       | Vapours may cause drowsiness and dizziness.  |

**16.4 Additional information**

The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oy, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

**Signature**

a/ome