

TEMACOAT GPL-S PRIMER

Date 12.8.2010

Previous date: 24.6.2008

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**1.1 Identification of the article**

1.1.1 Commercial Product Name
TEMACOAT GPL-S PRIMER

1.1.2 Product code
179 -series

1.2 Use of the Substance/Preparation**1.2.1 Intended use**

Painting work.

Description: A two component, polyamide-cured epoxy primer, base part.

1.3 Identification of the company**1.3.1 Supplier**

Tikkurila Oyj

1.3.2 Contact information:

P.O.Box P.O.Box 53
Postcode and post office FI-01301 VANTAA
FINLAND
Telephone +358 9 857 71
Telefax +358 9 8577 6936

1.3.4 Responsible for the Safety Data Sheet:

Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number**1.4.1 Telephone number, name and address**

Tikkurila Oyj, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION

Flammable.

Irritant, Xi

May cause sensitization by skin contact. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information on hazard labelling in section 15.1.

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Hazardous components**

3.1.1		3.1.2	3.1.3	3.1.4
CAS number	EINECS	Chemical name of the substance	Concentration	Classification
1330-20-7	215-535-7	Xylene	5 - 10 %	Xn; R10-20/21-38
25036-25-3	-	Epoxy resin (mw 700-1000)	10 - 20 %	Xi; R36/38-43
64742-95-6	265-199-0	Solvent naphtha, light aromatic	10 - 20 %	Xn, N; R10-37-65-66-67-51/53
1320-67-8	215-306-1	1-Methoxy-2-propanol	1 - 10 %	-; R10
68002-19-7	-	Ureaformaldehyde resin	0 - 2,5 %	-; R53
100-41-4	202-849-4	Ethylbenzene	1 - 5 %	F, Xn; R11-20
7779-90-0	231-994-3	Zinc phosphate	0 - 2,5 %	N; R50/53

3.1.7 Further information

Solvent naphtha, light aromatic contains benzene less than 0,1 w-%.

4. FIRST AID MEASURES

TEMACOAT GPL-S PRIMER

Date 12.8.2010

Previous date: 24.6.2008

4.1 Additional advice

In all cases of doubt, or when symptoms persist, seek medical attention.

4.2 Inhalation

Remove to fresh air, keep patient warm and at rest.

4.3 Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.

4.4 Eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

4.5 Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES**5.1 Suitable extinguishing media**

Use foam, CO₂, powder or water spray.

5.2 Extinguishing media which must not be used for safety reasons

Waterjet

5.3 Specific hazards

Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions**

Avoid breathing vapours. Exclude sources of ignition. Avoid skin contact with the product.

6.2 Environmental precautions

Do not allow to enter drains or water courses.

6.3 Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

7. HANDLING AND STORAGE**7.1 Handling**

Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges. Avoid skin contact.

7.2 Storage

Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 Exposure Limit Values****8.1.1 Occupational exposure limit values**

Xylene	100 ppm (8 h)
1-methoxy-2-propanol	100 ppm (8 h)
Ethylbenzene	100 ppm (8 h)

8.1.2 Information on limit values

TLV-TWA = Threshold Limit Values - Time-weighted average / ACGIH 2009

8.2 Exposure controls

TEMACOAT GPL-S PRIMER

Date 12.8.2010

Previous date: 24.6.2008

8.2.1 Occupational exposure controls

Provide adequate ventilation. Comply with the health and safety at work laws.

8.2.1.1 Respiratory protection

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.

8.2.1.2 Hand protection

Always wear approved protective gloves (e.g. nitrile rubber) against chemicals. Barrier creams may also help to protect the exposed areas of the skin.

8.2.1.3 Eye protection

Safety eyewear must be used, specially during spray-application.

8.2.1.4 Skin and body protection

Protective clothing must be used during spray-application.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 General Information (appearance, odour)**

Coloured, viscous liquid, strong odour.

9.2 Important Health Safety and Environmental Information

9.2.2 Boiling point/range 137 - 145 °C *)

9.2.3 Flash point 25 °C *)

9.2.5 Explosive properties

9.2.5.1 Lower explosion limit 1,0 vol-% *)

9.2.5.2 Upper explosion limit 7,0 vol-% *)

9.2.7 Vapour pressure 0,7 kPa (20 °C) *)

9.2.8 Relative density 1,4 - 1,5

9.2.9 Solubility

9.2.9.1 Water solubility Insoluble

9.2.11 Viscosity flow time more than 30 sec / ISO 3 mm cup

9.3 Other data

Evaporation rate (BuAc=1) : 0,76 *)

*) = Xylene

10. STABILITY AND REACTIVITY**10.1 Conditions to avoid**

Solvent vapours may form explosive mixtures with air.

10.2 Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.3 Hazardous decomposition products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION**11.1 Acute toxicity**

See section 11.5.

11.2 Primary irritation

See section 11.5.

11.3 Sensitisation

TEMACOAT GPL-S PRIMER

Date 12.8.2010

Previous date: 24.6.2008

Exposure by inhalation and skin contact may cause sensitization. Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin and respiratory sensitizer and an irritant. It contains epoxy constituents which are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies.

11.5 Human experience

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity****12.1.1 Aquatic toxicity**

Solvent naphtha, light aromatic: LC50 = 1-10 mg/l, fish, crustacean, algae (estimate); toxic

12.3 Persistence and degradability**12.3.1 Biodegradation**

Solvent naphtha, light aromatic: 78 %, 28 d; readily biodegradable

12.4 Bioaccumulative potential

Solvent naphtha, light aromatic: octanol/water partition coefficient log Pow = 3,7-4,5 (estimate)

12.6 Other adverse effects

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1	UN No	1263
14.2	Packing group	III
14.3	Land transport	
14.3.1	ADR/RID Class	3
14.3.3	Description of the goods	paint
14.3.4	Further Information	Drums/vessels < 450 litres: not subject to ADR because of high viscosity
14.4	Sea transport	
14.4.1	IMDG Class	3
14.4.2	Proper shipping name	paint
	Marine pollutant	no
14.4.3	Further Information	EmS: F-E,S-E Drums/vessels < 30 litres: Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.
14.5	Air transport	
14.5.1	ICAO/IATA Class	3

TEMACOAT GPL-S PRIMER

Date 12.8.2010

Previous date: 24.6.2008

14.5.2 Proper shipping name paint**15. REGULATORY INFORMATION****15.1 Information on the warning label****15.1.1 Letter code of the warning symbol and indications of danger for the preparation**

Xi Irritant

15.1.2 Names of the ingredients given on the warning label

Xylene

Solvent naphtha, light aromatic

Epoxy resin (mw 700-1000)

15.1.3 R-phrase(s)

R10 Flammable.

R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

15.1.4 S-phrase(s)

S23 Do not breathe vapour/spray.

S24 Avoid contact with skin.

S29 Do not empty into drains.

S37 Wear suitable gloves.

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

16. OTHER INFORMATION**16.1 Full text of R-phrases referred to under sections 2 and 3**

R11 Highly flammable.

R20 Harmful by inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10 Flammable.

R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R20/21 Harmful by inhalation and in contact with skin.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

16.4 Additional information

The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oyj, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

Signature

a/niear