

TEMADUR HB 50

Date 20.8.2010

Previous date: 6.8.2010

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**1.1 Identification of the article****1.1.1 Commercial Product Name**

TEMADUR HB 50

1.1.2 Product code

521 -series

1.2 Use of the Substance/Preparation**1.2.1 Intended use**

Painting work.

Description: A two component semi-gloss polyurethane paint

1.3 Identification of the company**1.3.1 Supplier**

Tikkurila Oyj

1.3.2 Contact information:**P.O.Box**

P.O.Box 53

Postcode and post office

FI-01301 VANTAA

FINLAND

Telephone

+358 9 857 71

Telefax

+358 9 8577 6936

1.3.4 Responsible for the Safety Data Sheet:

Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number**1.4.1 Telephone number, name and address**

Tikkurila Oyj, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION

Flammable.

Irritant; Xi

Dangerous for the environment, N

Irritating to respiratory system. May cause sensitization by skin contact. Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information on hazard labelling in section 15.1.

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Hazardous components****3.1.1****CAS number****EINECS****3.1.2****Chemical name of the substance****3.1.3****Concentration****3.1.4****Classification**

1330-20-7

215-535-7

Xylene

5 - 10 %

Xn; R10-20/21-38

64742-95-6

265-199-0

Solvent naphtha, light aromatic

10 - 25 %

Xn, N; R10-37-65-66-67-51/53

7779-90-0

231-994-3

Zinc phosphate

1 - 5 %

N; R50/53

41556-26-7/

255-437-1/

Pentamethyl piperidyl

< 0,5 %

Xi, N; R43-50/53

82919-37-7

280-060-4

sebacate

100-41-4

202-849-4

Ethylbenzene

1 - 5 %

F, Xn; R11-20

7429-90-5

231-072-3

Aluminium powder (stabilized)

0 - 5 %

F; R10-15

8052-41-3

232-489-3

Stoddard solvent

< 0,5 %

Xn, N; R10-65-66-67-51/53

-

-

Polyacrylate

5 - 10 %

Xi; R43

3.1.7 Further information

Solvent naphtha, light aromatic and Stoddard solvent contains benzene less than 0,1 w-%.

TEMADUR HB 50

Date 20.8.2010

Previous date: 6.8.2010

4. FIRST AID MEASURES

- 4.1 Additional advice**
In all cases of doubt, or when symptoms persist, seek medical attention.
- 4.2 Inhalation**
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.
- 4.4 Eye contact**
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- 4.5 Ingestion**
If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media**
Use foam, CO₂, powder or water spray.
- 5.2 Extinguishing media which must not be used for safety reasons**
Waterjet
- 5.3 Specific hazards**
Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions**
Avoid breathing vapours. Exclude sources of ignition.
- 6.2 Environmental precautions**
Do not allow to enter drains or water courses.
- 6.3 Methods for cleaning up**
Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

7. HANDLING AND STORAGE

- 7.1 Handling**
Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.
- 7.2 Storage**
Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.1 Exposure Limit Values**
- 8.1.1 Occupational exposure limit values**
- | | |
|-------------------------------|---------------------------|
| Xylene | 100 ppm (8 h) |
| Ethylbenzene | 100 ppm (8 h) |
| Stoddard solvent | 100 ppm (8 h) |
| Aluminium powder (stabilized) | 1 mg/m ³ (8 h) |

TEMADUR HB 50

Date 20.8.2010

Previous date: 6.8.2010

8.1.2 Information on limit values

TLV-TWA = Threshold Limit Values - Time-weighted average / ACGIH 2009

8.2 Exposure controls**8.2.1 Occupational exposure controls**

Provide adequate ventilation. Comply with the health and safety at work laws.

8.2.1.1 Respiratory protection

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.

8.2.1.2 Hand protection

Always wear protective gloves (e.g. nitrile rubber). Barrier creams may also help to protect the exposed areas of the skin.

8.2.1.3 Eye protection

Safety eyewear must be used, specially during spray-application.

8.2.1.4 Skin and body protection

Protective clothing must be used during spray-application.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 General Information (appearance, odour)**

Coloured, viscous liquid, strong odour.

9.2 Important Health Safety and Environmental Information**9.2.2 Boiling point/range** 137 - 145 °C *)**9.2.3 Flash point** 25 °C *)**9.2.5 Explosive properties****9.2.5.1 Lower explosion limit** 1,0 vol-% *)**9.2.5.2 Upper explosion limit** 7,0 vol-% *)**9.2.7 Vapour pressure** 0,7 kPa (20 °C) *)**9.2.8 Relative density** 1,3 - 1,4**9.2.9 Solubility****9.2.9.1 Water solubility** Insoluble**9.2.11 Viscosity** flow time more than 30 sec / ISO 3 mm cup**9.3 Other data**

Evaporation rate (BuAc=1) : 0,76 *)

*) =Xylene

10. STABILITY AND REACTIVITY**10.1 Conditions to avoid**

Solvent vapours may form explosive mixtures with air.

10.2 Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.3 Hazardous decomposition products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION**11.1 Acute toxicity**

See section 11.5.

11.2 Primary irritation

See section 11.5.

TEMADUR HB 50

Date 20.8.2010

Previous date: 6.8.2010

11.3 Sensitisation

May cause sensitization by skin contact.

11.5 Human experience

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity****12.1.1 Aquatic toxicity**

Zinc phosphate: LC50(fish) = 0,14-2,6 mg Zn²⁺/l; EC50(48h, daphnia magna) = 0,04-0,86 mg Zn²⁺/l, EC50 (72h, algae) = 0,136-0,150 mg Zn²⁺/l

Solvent naphtha, light aromatic: LC50 = 1-10 mg/l, fish, crustacean, algae (estimate); toxic

12.3 Persistence and degradability**12.3.1 Biodegradation**

Solvent naphtha, light aromatic: 78 %, 28 d; readily biodegradable

12.4 Bioaccumulative potential

Solvent naphtha, light aromatic: octanol/water partition coefficient log Pow = 3,7-4,5 (estimate)

12.6 Other adverse effects

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1	UN No	1263
14.2	Packing group	III
14.3	Land transport	
14.3.1	ADR/RID Class	3
14.3.3	Description of the goods	paint
14.4	Sea transport	
14.4.1	IMDG Class	3
14.4.2	Proper shipping name	paint
	Marine pollutant	yes
14.4.3	Further Information	EmS: F-E,S-E
14.5	Air transport	
14.5.1	ICAO/IATA Class	3
14.5.2	Proper shipping name	paint

15. REGULATORY INFORMATION

TEMADUR HB 50

Date 20.8.2010

Previous date: 6.8.2010

15.1	Information on the warning label
15.1.1	Letter code of the warning symbol and indications of danger for the preparation
	Xi Irritant
	N Dangerous for the environment
15.1.2	Names of the ingredients given on the warning label
	Xylene
	Zinc phosphate
	Solvent naphtha, light aromatic
	Polyacrylate
15.1.3	R-phrase(s)
	R10 Flammable.
	R37 Irritating to respiratory system.
	R43 May cause sensitization by skin contact.
	R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R67 Vapours may cause drowsiness and dizziness.
15.1.4	S-phrase(s)
	S23 Do not breathe vapour/spray.
	S24 Avoid contact with skin.
	S29 Do not empty into drains.
	S37 Wear suitable gloves.
	S38 In case of insufficient ventilation, wear suitable respiratory equipment.

16. OTHER INFORMATION

16.1	Full text of R-phrases referred to under sections 2 and 3
	R11 Highly flammable.
	R20 Harmful by inhalation.
	R10 Flammable.
	R37 Irritating to respiratory system.
	R43 May cause sensitization by skin contact.
	R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R15 Contact with water liberates extremely flammable gases.
	R20/21 Harmful by inhalation and in contact with skin.
	R67 Vapours may cause drowsiness and dizziness.
	R38 Irritating to skin.
	R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R65 Harmful: may cause lung damage if swallowed.
	R66 Repeated exposure may cause skin dryness or cracking.
16.4	Additional information
	The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.
	Additional information available from: Tikkurila Oyj, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com
	Signature a/niear