

HARDENER 008 7605

Date 8.10.2008

Previous date: 4.4.2008

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 Identification of the article**
1.1.1 Commercial Product Name
HARDENER 008 7605
- 1.1.2 Product code**
008 7605
- 1.2 Use of the Substance/Preparation**
1.2.1 Intended use
Painting work.
Description: Isocyanate hardener
- 1.3 Identification of the company**
1.3.1 Supplier
Tikkurila Oyj
- 1.3.2 Contact information:**
P.O.Box P.O.Box 53
Postcode and post office FI-01301 VANTAA
FINLAND
Telephone +358 9 857 71
Telefax +358 9 8577 6936
- 1.3.4 Responsible for the Safety Data Sheet:**
Tikkurila Oy, Product Safety, e-mail: productsafety@tikkurila.com
- 1.4 Emergency telephone number**
1.4.1 Telephone number, name and address
Tikkurila Oy, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION

Harmful, Xn

Harmful by inhalation and in contact with skin. May cause sensitization by skin contact.

Information on hazard labelling in section 15.1.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1	Hazardous components		3.1.2 Chemical name of the substance	3.1.3 Concentration	3.1.4 Classification
	3.1.1 CAS number	EINECS			
	112-07-2	203-933-3	Butylglycol acetate	25 - 50 %	Xn; R20/21
	28182-81-2	-	Isocyanate resin	50 - 75 %	Xn; R43
	822-06-0	212-485-8	Hexamethylene-1,6-di- isocyanate (HDI)	< 0,5 %	T; R23-36/37/38-42/43

4. FIRST AID MEASURES

- 4.1 Additional advice**
In all cases of doubt, or when symptoms persist, seek medical attention.
- 4.2 Inhalation**
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.
- 4.4 Eye contact**
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

HARDENER 008 7605

Date 8.10.2008

Previous date: 4.4.2008

4.5 Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES**5.1 Suitable extinguishing media**

Use foam, CO₂, powder or water spray.

5.2 Extinguishing media which must not be used for safety reasons

Waterjet

5.3 Specific hazards

Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions**

Avoid breathing vapours. Exclude sources of ignition. Avoid skin contact with the product.

6.2 Environmental precautions

Do not allow to enter drains or water courses.

6.3 Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts) / ethanol or isopropanol (50 parts) / concentrated ammonia (5 parts). A non-flammable alternative is sodium carbonate (5 parts) / water (95 parts). Add the same decontaminant to the remnants and let stand for several days in non-sealed container until no further reaction. Once this stage is reached, close container and dispose of according to local regulations.

7. HANDLING AND STORAGE**7.1 Handling**

Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.

7.2 Storage

Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight. Precautions should be taken to minimize exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Care should be taken when re-opening partly used containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 Exposure Limit Values****8.1.1 Occupational exposure limit values**

Butylglycol acetate	20 ppm (8 h)
Hexamethylene-1,6-di-isocyanate (HDI)	0,005 ppm (8 h)

8.1.2 Information on limit values

TLV-TWA = Threshold Limit Values - Time-weighted average / ACGIH 2007

8.2 Exposure controls**8.2.1 Occupational exposure controls**

Provide adequate ventilation. When handling paints containing isocyanates all precautions required for solvent-containing paints must be followed. Vapour and spray mist in particular should not be inhaled. Allergics and asthmatics as well as people prone to respiratory ailments should not work with isocyanate containing paints. Comply with the health and safety at work laws.

8.2.1.1 Respiratory protection

HARDENER 008 7605

Date 8.10.2008

Previous date: 4.4.2008

If ventilation is insufficient, use appropriate certified respirators with gas, vapour and dust filter AP. During spray-application or during continuous and long-term work, an air-fed protective respiratory equipment must be worn even when good ventilation is provided.

8.2.1.2 Hand protection

Always wear approved protective gloves (e.g. butyl or fluoro rubber) against chemicals. Barrier creams may also help to protect the exposed areas of the skin.

8.2.1.3 Eye protection

Safety eyewear must be used, specially during spray-application.

8.2.1.4 Skin and body protection

Use suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 General Information (appearance, odour)**

Viscous liquid, strong odour

9.2 Important Health Safety and Environmental Information

9.2.2 Boiling point/range 192 °C *)

9.2.3 Flash point + 71 °C

9.2.5 Explosive properties

9.2.5.1 Lower explosion limit 0,5 vol-% *)

9.2.5.2 Upper explosion limit 8,5 vol-% *)

9.2.7 Vapour pressure 0,027 kPa (20 °C) *)

9.2.8 Relative density 1,1

9.2.9 Solubility

9.2.9.1 Water solubility Insoluble

9.3 Other data

Evaporation rate (BuAc=1) : 0,03 *)

*) = Butylglycol acetate

10. STABILITY AND REACTIVITY**10.1 Conditions to avoid**

Solvent vapours may form explosive mixtures with air.

10.2 Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials, amines and alcohols. Uncontrolled exothermic reactions occur with amines and alcohols. Reacts with water resulting in evolution of carbon dioxide (CO₂). In closed containers, the pressure build up could result in bursting of the container.

10.3 Hazardous decomposition products

Fire will produce dense black smoke. Hazardous decomposition products, such as smoke, carbon monoxide, oxides of nitrogen, hydrogen cyanide and isocyanate compounds, may be produced in a fire or when exposed to high temperatures -e.g. when welding or flame cutting a painted surface. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION**11.1 Acute toxicity**

See section 11.5

11.2 Primary irritation

See section 11.5.

11.3 Sensitisation

HARDENER 008 7605

Date 8.10.2008

Previous date: 4.4.2008

Exposure by inhalation and skin contact may cause sensitization. Based on the properties of the isocyanate components and considering toxicological data on similar preparations, this preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability.

11.5 Human experience

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally.

12. ECOLOGICAL INFORMATION**12.6 Other adverse effects**

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

The hardener reacts with water resulting in evolution of carbon dioxide (CO₂). The ready for use mixture of paint and hardener will form carbon dioxide which in closed containers can result in pressurisation.

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1	UN No	-
14.2	Packing group	-
14.3	Land transport	
14.3.1	ADR/RID Class	not classified
14.4	Sea transport	
14.4.1	IMDG Class	not classified
14.5	Air transport	
14.5.1	ICAO/IATA Class	not classified

15. REGULATORY INFORMATION**15.1 Information on the warning label****15.1.1 Letter code of the warning symbol and indications of danger for the preparation**

Xn Harmful

15.1.2 Names of the ingredients given on the warning label

Isocyanate resin
Butylglycol acetate

15.1.3 R-phrases(s)

R20/21 Harmful by inhalation and in contact with skin.
R43 May cause sensitization by skin contact.

15.1.4 S-phrases(s)

S23 Do not breathe vapour/spray.
S24 Avoid contact with skin.

HARDENER 008 7605

Date 8.10.2008

Previous date: 4.4.2008

S36/37 Wear suitable protective clothing and gloves.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

15.1.5 Special regulations on certain preparations

Contains isocyanates. See information supplied by the manufacturer.

16. OTHER INFORMATION**16.1 Full text of R-phrases referred to under sections 2 and 3**

R20/21 Harmful by inhalation and in contact with skin.
R43 May cause sensitization by skin contact.
R23 Toxic by inhalation.
R36/37/38 Irritating to eyes, respiratory system and skin.
R42/43 May cause sensitization by inhalation and skin contact.

16.4 Additional information

The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oy, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

Signature

d2/ome