

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier****1.1.1 Commercial Product Name**
TEMABLAST EV 110 HARDENER**1.1.2 Product code**
008 7929**1.2 Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Recommended use**Painting work.
Description: Polyamide hardener**1.3 Details of the supplier of the safety data sheet****1.3.1 Supplier**

Tikkurila Oyj

P.O.Box

P.O.Box 53

Postcode and post officeFI-01301 VANTAA
FINLAND**Telephone**

+358 9 857 71

Telefax

+358 9 8577 6936

1.3.4 Responsible for the Safety Data Sheet:

Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number**1.4.1 Telephone number, name and address**

Tikkurila Oyj, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****67/548/EEC - 1999/45/EC**
F, Xn; R11-36/38-48/20-63-65-67**2.2 Label elements****67/548/EEC - 1999/45/EC**

F Highly flammable

Xn Harmful

**R-phrases(s)**

R11 Highly flammable.

R36/38 Irritating to eyes and skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

S-phrases(s)

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S29 Do not empty into drains.

S33 Take precautionary measures against static discharges.

S36/37 Wear suitable protective clothing and gloves.

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

Contains:

Polyaminoamide, toluene and acetone.

Special regulations on certain preparations

Contains triethylenetetramine. May produce an allergic reaction.

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

- 2.3 Other hazards**
Other hazards are not known.

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

CAS number	EINECS	Chemical name of the substance	Concentration	Classification
108-88-3	203-625-9	Toluene	50 - 75 %	F, Xn; R11-38-48/20-63-65-67
67-63-0	200-661-7	Isopropanol	10 - 25 %	F, Xi; R11-36-67
68410-23-1	-	Polyaminoamide	5 - 10 %	Xi; R41
1330-20-7	215-535-7	Xylene	5 - 10 %	Xn; R10-20/21-38
67-64-1	200-662-2	Acetone	5 - 10 %	F, Xi; R11-36-66-67
107-98-2	203-539-1	1-Methoxy-2-propanol	1 - 5 %	-; R10-67
100-41-4	202-849-4	Ethylbenzene	1 - 5 %	F, Xn; R11-20
112-24-3	203-950-6	Triethylenetetramine	< 1 %	C; R21-34-43-52/53

3.3 Other information

See Section 16 for full text of R-phrases and H-statements.

4. FIRST AID MEASURES**4.1 Description of first aid measures**

In all cases of doubt, or when symptoms persist, seek medical attention.

4.1.2 Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Seek medical attention.

4.1.3 Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.

4.1.4 Eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 15 minutes and seek medical advice if necessary.

4.1.5 Ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

4.3 Indication of immediate medical attention and special treatment needed

None.

5. FIREFIGHTING MEASURES**5.1 Extinguishing media****5.1.1 Suitable extinguishing media**

Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.

5.1.2 Extinguishing media which must not be used for safety reasons

Do not use strong water jets.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter drains or water courses.

6.3 Methods and materials for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

6.4 Reference to other sections

See also Section 13 for waste disposal instructions.

7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Vapours are heavier than air and may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Isolate from sources of heat, sparks and open flame. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. No sparking tools should be used. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area.

Risk of self-ignition! Materials such as cleaning rags and paper wipes, which are contaminated with the product, sanding dust or overspray containing the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be placed in a container soaked with water or laid out flat in a single layer to dry preferably outdoors or incinerated immediately. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition. No smoking. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. Keep container tightly closed.

7.3 Specific end use(s)

None.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****8.1.1 Occupational exposure limit values**

Toluene (TLV)	20 ppm (8 h)	
Toluene (EU)	50 ppm (8 h)	100 ppm (15 min)
	Skin	
Isopropanol	200 ppm (8 h)	400 ppm (15 min)
Xylene (TLV)	100 ppm (8 h)	150 ppm (15 min)
Xylene (EU)	50 ppm (8 h)	100 ppm (15 min)
	Skin	
Acetone (TLV)	500 ppm (8 h)	750 ppm (15 min)
Acetone (EU)	500 ppm (8 h)	

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

1-Methoxy-2-propanol (TLV)	100 ppm (8 h)	150 ppm (15 min)
1-Methoxy-2-propanol (EU)	100 ppm (8 h)	150 ppm (15 min)
	Skin	
Ethylbenzene (TLV)	100 ppm (8 h)	125 ppm (15 min)
Ethylbenzene (EU)	100 ppm (8 h)	200 ppm (15 min)
	Skin	

8.1.2 Other information on limit values

TLV = Threshold Limit Values according to ACGIH 2009 (American Conference of Governmental Industrial Hygienists)

EU = Occupational Exposure Limit Values according to EU Directives 1998/24/EC, 2000/39/EC, 2006/15/EC, 2009/161/EU.

Skin = A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

8.2 Exposure controls**8.2.1 Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.2.2 Individual protection measures**8.2.2.1 Respiratory protection**

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter A/P3. During continuous and long-term work the use of motor-driven or air-fed respirators is recommended.

8.2.2.2 Hand protection

Always wear approved protective gloves against chemicals.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Gloves should be replaced regularly. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended protective glove type is e.g.:

nitrile rubber (splash protection),

butyl rubber (splash protection),

laminated foil (breakthrough time > 480 min.)

PVC or natural rubber gloves are not recommended.

8.2.2.3 Eye/face protection

Use safety eyewear designed to protect against splash of liquids.

8.2.2.4 Skin protection

Personnel should wear protective clothing.

When necessary, wear anti-static protective clothing made of natural fibre or of high temperature resistant synthetic fibre.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Important Health Safety and Environmental Information****9.1.1 Appearance**

Viscous liquid, strong odour

9.1.6 Initial boiling point and boiling range 56 °C *)

9.1.7 Flash point -18 °C *)

9.1.10 Explosive properties

9.1.10.1 Lower explosion limit 2,2 vol-% *)

9.1.10.2 Upper explosion limit 13 vol-% *)

9.1.11 Vapour pressure 24 kPa (26 °C) *)

9.1.13 Relative density 0,9

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

- 9.1.14 Solubility(ies)**
9.1.14.1 Water solubility Insoluble
- 9.2 Other information**
Evaporation rate (BuAc=1) : 5,6 *
*) = Acetone

10. STABILITY AND REACTIVITY

- 10.1 Reactivity**
See section 10.5.
- 10.2 Chemical stability**
Stable under recommended storage and handling conditions (see section 7).
- 10.3 Possibility of hazardous reactions**
See section 10.5.
- 10.4 Conditions to avoid**
In confined or poorly ventilated spaces solvent vapours may form explosive mixtures with air. When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials**
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- 10.6 Hazardous decomposition products**
Hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. may produce when exposed to high temperatures.

11. TOXICOLOGICAL INFORMATION

- 11.1 Information on toxicological effects**
There are no toxicological test data available on the product itself.
- 11.1.3 Sensitisation**
Contains triethylenetetramine. May produce an allergic reaction.
- 11.1.4 Carcinogenicity, mutagenicity or reproductive toxicity**
The product contains toluene. Possible risk of harm to the unborn child.
- 11.1.6 Specific target organ toxicity - repeated exposure**
The product contains toluene, which is classified as harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 11.1.7 Aspiration hazard**
The product contains toluene, which may cause lung damage if swallowed.
- 11.1.8 Other information on acute toxicity**
Inhalation: Long term exposure to spray mist or solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Skin contact: Repeated or prolonged contact with the preparation causes removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashed in the eyes cause eye irritation.
Ingestion: Ingestion may cause nausea, diarrhoea and vomiting.

12. ECOLOGICAL INFORMATION

- 12.1 Toxicity**
12.1.1 Aquatic toxicity
No relevant data.

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

12.2 Persistence and degradability**12.2.1 Biodegradation**

No relevant data.

12.3 Bioaccumulative potential

No relevant data.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

There is no ecotoxicological test data available on the product itself. The product should not be allowed to enter drains or water courses. The product is not classified as environmentally hazardous.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods****Product residues:**

Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

Packaging waste:

Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION**14.1 UN number** 1263**14.2 UN proper shipping name** paint related material**14.3 Transport hazard class(es)** 3**14.4 Packing group** II**14.5 Environmental hazards**

The product is not classified as environmentally hazardous according to international transport regulations.

14.6 Special precautions for users

None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

None known.

14.8 Further Information

EmS: F-E,S-E

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None known.

15.2 Chemical safety assessment

Has not been performed.

16. OTHER INFORMATION**16.5 Full text of R-phrases and/or Hazard statements (H-statements) referred to under sections 2 and 3**

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

TEMABLAST EV 110 HARDENER

Date 21.9.2011

Previous date: 26.3.2009

R20/21	Harmful by inhalation and in contact with skin.
R21	Harmful in contact with skin.
R34	Causes burns.
R36	Irritating to eyes.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitization by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

16.8**Additional information**

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 453/2010 to Regulation (EC) No 1907/2006 (REACH).

The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Additional information available from:

Tikkurila Oyj, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND,
Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

Signature

ad/mom