

TEMAFLOOR 150 epoxy paint

Date 29.5.2008

Previous date: 2.11.2006

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 Identification of the article**
- 1.1.1 Commercial Product Name**
TEMAFLOOR 150 epoxy paint
- 1.1.2 Product code**
102 -series
- 1.2 Use of the Substance/Preparation**
- 1.2.1 Intended use**
Painting work
Description:A two-component solvent-free epoxy paint
- 1.3 Identification of the company**
- 1.3.1 Supplier**
Tikkurila Oyj
- 1.3.2 Contact information:**
- P.O.Box** P.O.Box 53
Postcode and post office FI-01301 VANTAA
FINLAND
- Telephone** +358 9 857 71
Telefax +358 9 8577 6936
- 1.3.4 Responsible for the Safety Data Sheet:**
Tikkurila Oy, Product Safety, e-mail: productsafety@tikkurila.com
- 1.4 Emergency telephone number**
- 1.4.1 Telephone number, name and address**
Tikkurila Oy, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION

Irritant; Xi
Dangerous for the environment, N
May cause sensitization by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Information on hazard labelling in section 15.1.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1	Hazardous components		3.1.2	3.1.3	3.1.4
3.1.1	CAS number	EINECS	Chemical name of the substance	Concentration	Classification
	25068-38-6	500-033-5	Epoxy resin (mw < 700)	25 - 50 %	Xi, N; R36/38-43-51/53
	68081-84-5	268-358-2	Glycidyl ether	1 - 10 %	Xi, N; R36/38-43-51/53
	100-51-6	202-859-9	Benzyl alcohol	1 - 5 %	Xn; R20/22
	9072-62-2	-	Propylene glycol diglycidyl ether	0 - 2,5 %	Xi; R36/38-43
	64742-95-6	265-199-0	Solvent naphtha, light aromatic	< 1 %	Xn, N; R10-37-65-66-67-51/53

4. FIRST AID MEASURES

- 4.1 Additional advice**
In all cases of doubt, or when symptoms persist, seek medical attention.

TEMAFLOOR 150 epoxy paint

Date 29.5.2008

Previous date: 2.11.2006

- 4.2 Inhalation**
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.
- 4.4 Eye contact**
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- 4.5 Ingestion**
If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media**
Use foam, CO₂, powder or water spray.
- 5.2 Extinguishing media which must not be used for safety reasons**
Waterjet
- 5.3 Specific hazards**
Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions**
Avoid skin contact with the product.
- 6.2 Environmental precautions**
Do not allow to enter drains or water courses.
- 6.3 Methods for cleaning up**
Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

7. HANDLING AND STORAGE

- 7.1 Handling**
Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.
- 7.2 Storage**
Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.2 Exposure controls**
- 8.2.1 Occupational exposure controls**
Provide adequate ventilation. Skin contact with the preparation should be avoided, when handling products, which contain epoxy resin. Comply with the health and safety at work laws.
- 8.2.1.1 Respiratory protection**
Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient.
- 8.2.1.2 Hand protection**
Always wear approved protective gloves (e.g. nitrile rubber) against chemicals. Barrier creams may also help to protect the exposed areas of the skin.
- 8.2.1.3 Eye protection**
Safety eyewear must be used, specially during the mixing of the components.

TEMAFLOOR 150 epoxy paint

Date 29.5.2008

Previous date: 2.11.2006

- 8.2.1.4 Skin and body protection**
Use suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- 9.1 General Information (appearance, odour)**
Coloured, viscous liquid
- 9.2 Important Health Safety and Environmental Information**
- 9.2.2 Boiling point/range** -
- 9.2.3 Flash point** -
- 9.2.5 Explosive properties**
- 9.2.5.1 Lower explosion limit** -
- 9.2.5.2 Upper explosion limit** -
- 9.2.7 Vapour pressure** -
- 9.2.8 Relative density** 1,82 - 1,86
- 9.2.9 Solubility**
- 9.2.9.1 Water solubility** Insoluble

10. STABILITY AND REACTIVITY

- 10.1 Conditions to avoid**
If solvents are used to lower the viscosity, it should be noticed, that solvent vapours may form explosive mixtures with air.
- 10.2 Materials to avoid**
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- 10.3 Hazardous decomposition products**
Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION

- 11.1 Acute toxicity**
See section 11.5.
- 11.2 Primary irritation**
See section 11.5.
- 11.3 Sensitisation**
Exposure by inhalation and skin contact may cause sensitization. Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin and respiratory sensitizer and an irritant. It contains low molecular epoxy constituents which are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies.
- 11.5 Human experience**
- 11.5.1 Inhalation: Long term exposure causes irritation of respiratory system and mucous membranes of nose and throat.
- 11.5.2 Skin contact: Splashes may cause skin and eye irritation.
- 11.5.3 Other effects: Harmful if taken internally.

12. ECOLOGICAL INFORMATION

- 12.1 Ecotoxicity**
- 12.1.1 Aquatic toxicity**

TEMAFLOOR 150 epoxy paint

Date 29.5.2008

Previous date: 2.11.2006

Epoxy resin (mw < 700): LC50 = 1,5-7,7 mg/l, onchorynchus mykiss; toxic.
 EC50 = 1,0 mg/l, daphnia magna; toxic.
 IC50 = 18 mg/l, green algae (selenastrum capricornutum), 72 h; harmful

12.3 Persistence and degradability**12.3.1 Biodegradation**

Epoxy resin (mw < 700): 2-3 %, 28 d, OECD 301D

12.4 Bioaccumulative potential

Epoxy resin (mw < 700): octanol/water partition coefficient log Pow = 2,8-4

12.6 Other adverse effects

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances). The ready for use mixture of paint and hardener generates much heat. Allow the remainder of the mixture to harden in a safe place, e.g. in the open.

13.2 Packaging: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1	UN No	3082
14.2	Packing group	III
14.3	Land transport	
14.3.1	ADR/RID Class	9
14.3.3	Description of the goods	environmentally hazardous substance, liquid, N.O.S. (epoxy resin)
14.4	Sea transport	
14.4.1	IMDG Class	9
14.4.2	Proper shipping name	environmentally hazardous substance, liquid, N.O.S. (epoxy resin)
14.4.3	Further Information	EmS: F-A,S-F
14.5	Air transport	
14.5.1	ICAO/IATA Class	9
14.5.2	Proper shipping name	environmentally hazardous substance, liquid, N.O.S. (epoxy resin)

15. REGULATORY INFORMATION**15.1 Information on the warning label****15.1.1 Letter code of the warning symbol and indications of danger for the preparation**

Xi Irritant
 N Dangerous for the environment

15.1.2 Names of the ingredients given on the warning label

Epoxy resin (mw < 700)
 Glycidyl ether

15.1.3 R-phrases

R36/38 Irritating to eyes and skin.
 R43 May cause sensitization by skin contact.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

TEMAFLOOR 150 epoxy paint

Date 29.5.2008

Previous date: 2.11.2006

- 15.1.4 S-phrase(s)**
- | | |
|-----------|---|
| S2 | Keep out of reach of children. |
| S24 | Avoid contact with the skin. |
| S26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S29 | Do not empty into drains. |
| S36/37/39 | Wear suitable protective clothing, gloves and eye/face protection. |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |
| S51 | Use only in well ventilated areas. |

15.1.5 Special regulations on certain preparations

Contains epoxy constituents. See information supplied by the manufacturer.

16. OTHER INFORMATION**16.1 Full text of R-phrases referred to under sections 2 and 3**

- | | |
|--------|---|
| R36/38 | Irritating to eyes and skin. |
| R43 | May cause sensitization by skin contact. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R10 | Flammable. |
| R20/22 | Harmful by inhalation and if swallowed. |
| R37 | Irritating to respiratory system. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |

16.4 Additional information

The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oy, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

Signature

f3/ome