

YLEISOHENNE 1060 (UNIVERSAL THINNER)

Date 27.10.2010

Previous date: -

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**1.1 Identification of the article****1.1.1 Commercial Product Name**

YLEISOHENNE 1060 (UNIVERSAL THINNER)

1.1.2 Product code

006 1060

1.2 Use of the Substance/Preparation**1.2.1 Intended use**Painting work.
Description: Thinner**1.3 Identification of the company****1.3.1 Supplier**

Tikkurila Oyj

1.3.2 Contact information:**P.O.Box**

P.O.Box 53

Postcode and post officeFI-01301 VANTAA
FINLAND**Telephone**

+358 9 857 71

Telefax

+358 9 8577 6936

1.3.4 Responsible for the Safety Data Sheet:

Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number**1.4.1 Telephone number, name and address**

Tikkurila Oyj, Environment and Safety: +358 9 857 71

2. HAZARDS IDENTIFICATION

Highly flammable.

Harmful, Xn

Dangerous for the environment, N

Irritating to eyes and skin. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Information on hazard labelling in section 15.1.

3. COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Hazardous components****3.1.1****CAS number****EINECS****3.1.2****Chemical name of the substance****3.1.3****Concentration****3.1.4****Classification**

67-64-1

200-662-2

Acetone

25 - 50 %

F, Xi; R11-36-66-67

64-17-5

200-578-6

Ethanol

10 - 25 %

F; R11

64742-49-0

265-151-9

Naphtha, hydrotreated light
(aliphatic)

25 - 50 %

F, Xn, N; R11-38-65-67-51/53

3.1.7 Further information

Naphtha, hydrotreated light (aliphatic) contains benzene less than 0,1 w-%.

4. FIRST AID MEASURES**4.1 Additional advice**

In all cases of doubt, or when symptoms persist, seek medical attention.

YLEISOHENNE 1060 (UNIVERSAL THINNER)

Date 27.10.2010

Previous date: -

- 4.2 Inhalation**
Remove to fresh air, keep patient warm and at rest.
- 4.3 Skin contact**
Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser.
- 4.4 Eye contact**
Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- 4.5 Ingestion**
If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media**
Use foam, CO₂, powder or water spray.
- 5.2 Extinguishing media which must not be used for safety reasons**
Waterjet
- 5.3 Specific hazards**
Fire will produce dense black smoke, which contains decomposition products. Avoid breathing the smoke.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions**
Avoid breathing vapours. Exclude sources of ignition.
- 6.2 Environmental precautions**
Do not allow to enter drains or water courses.
- 6.3 Methods for cleaning up**
Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents. Note! Products containing oxidative drying oil or alkyd (linseed oil varnish, alkyd paints and -lacquers) have a possibility of self-ignition in porous materials damped by the product. This kind of waste must be collected and stored e.g. in water before disposal or incinerated immediately.

7. HANDLING AND STORAGE

- 7.1 Handling**
Vapours are heavier than air and may form explosive mixtures with air. Good ventilation must be provided. Keep away from sources of ignition. Take precautionary measures against static discharges.
- 7.2 Storage**
Keep containers tightly closed. Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- 8.1 Exposure Limit Values**
- 8.1.1 Occupational exposure limit values**
- | | |
|-----------------------|----------------|
| Acetone (TLV-TWA, EU) | 500 ppm (8 h) |
| Ethanol (TLV-STEL) | 1000 ppm (8 h) |
- 8.1.2 Information on limit values**
TLV-STEL = Threshold Limit Values - Short-term exposure limit according to ACGIH 2009 (American Conference of Governmental Industrial Hygienists)
EU = Occupational Exposure Limit Values according to EU Directives 1998/24/EC, 2000/39/EC, 2006/15/EC, 2009/161/EU.

YLEISOHENNE 1060 (UNIVERSAL THINNER)

Date 27.10.2010

Previous date: -

8.2 Exposure controls**8.2.1 Occupational exposure controls**

Provide adequate ventilation. Comply with the health and safety at work laws.

8.2.1.1 Respiratory protection

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter AP. During continuous and long-term work the use of air-fed or motor-driven respirators is recommended.

8.2.1.2 Hand protection

Always wear protective gloves (e.g. nitrile rubber). Barrier creams may also help to protect the exposed areas of the skin.

8.2.1.3 Eye protection

Safety eyewear must be used, specially during spray-application.

8.2.1.4 Skin and body protection

Protective clothing must be used during spray-application.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 General Information (appearance, odour)**

Neste, voimakas haju

9.2 Important Health Safety and Environmental Information

9.2.2 Boiling point/range 56 °C *)

9.2.3 Flash point -10 °C

9.2.5 Explosive properties

9.2.5.1 Lower explosion limit 2,2 vol-% *)

9.2.5.2 Upper explosion limit 13 vol-% *)

9.2.7 Vapour pressure 24 kPa (20°C) *)

9.2.8 Relative density 0,75

9.2.9 Solubility

9.2.9.1 Water solubility partly soluble

9.3 Other data

Evaporation rate (BuAc=1) : 5,6 *)

*) = Acetone

10. STABILITY AND REACTIVITY**10.1 Conditions to avoid**

Solvent vapours may form explosive mixtures with air.

10.2 Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.3 Hazardous decomposition products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

11. TOXICOLOGICAL INFORMATION**11.1 Acute toxicity**

See section 11.5.

11.2 Primary irritation

See section 11.5.

11.3 Sensitisation

YLEISOHENNE 1060 (UNIVERSAL THINNER)

Date 27.10.2010

Previous date: -

11.5 Human experience

11.5.1 Inhalation: Solvent vapours and spray mist harmful if inhaled. Long term exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache and dizziness.

11.5.2 Skin contact: Repeated or prolonged contact with the preparation may cause removal of the natural fat from the skin resulting in contact dermatitis. Splashes in the eyes may cause irritation.

11.5.3 Other effects: Harmful if taken internally. The product contains solvent naphtha, which may cause lung damage if swallowed.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity****12.1.1 Aquatic toxicity**

Naphtha, hydrotreated light: LL50 = 11 mg/l, fish, algae, daphnia magna; harmful

12.3 Persistence and degradability**12.3.1 Biodegradation**

Naphtha, hydrotreated light: readily biodegradable (estimate)

12.4 Bioaccumulative potential

Naphtha, hydrotreated light: octanol/water partition coefficient log Kow = 2-7

12.6 Other adverse effects

There is no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

13. DISPOSAL CONSIDERATIONS

13.1 Product residues: Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).

13.2 Packaging waste: Empty cans should be recycled or disposed of in accordance with local regulations.

14. TRANSPORT INFORMATION

| | | |
|---------------|---------------------------------|------------------------|
| 14.1 | UN No | 1263 |
| 14.2 | Packing group | II |
| 14.3 | Land transport | |
| 14.3.1 | ADR/RID Class | 3 |
| 14.3.3 | Description of the goods | paint related material |
| 14.4 | Sea transport | |
| 14.4.1 | IMDG Class | 3 |
| 14.4.2 | Proper shipping name | paint related material |
| | Marine pollutant | kyllä |
| 14.4.3 | Further Information | EmS: F-E, S-E |
| 14.5 | Air transport | |
| 14.5.1 | ICAO/IATA Class | 3 |
| 14.5.2 | Proper shipping name | paint related material |

15. REGULATORY INFORMATION**15.1 Information on the warning label****15.1.1 Letter code of the warning symbol and indications of danger for the preparation**

YLEISOHENNE 1060 (UNIVERSAL THINNER)

Date 27.10.2010

Previous date: -

F Highly flammable
Xn Harmful
N Dangerous for the environment

15.1.2 Names of the ingredients given on the warning label

Naphtha, hydrotreated light (aliphatic)
Acetone

15.1.3 R-phrases

R11 Highly flammable.
R36/38 Irritating to eyes and skin.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

15.1.4 S-phrases

S2 Keep out of the reach of children.
S16 Keep away from sources of ignition - No smoking.
S23 Do not breathe vapour/spray.
S29 Do not empty into drains.
S33 Take precautionary measures against static discharges.
S51 Use only in well-ventilated areas.
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION**16.1 Full text of R-phrases referred to under sections 2 and 3**

R11 Highly flammable.
R36/38 Irritating to eyes and skin.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R36 Irritating to eyes.
R38 Irritating to skin.
R66 Repeated exposure may cause skin dryness or cracking.

16.4 Additional information

The information of this MSDS is based on the present state of our knowledge and on current EC laws. It is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the products' properties.

Additional information available from: Tikkurila Oyj, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND, Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: productsafety@tikkurila.com

Signature

a/akk