

**WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)**

Date 26.7.2011

Previous date: 3.12.2010

**1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier****1.1.1 Commercial Product Name**

WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)

**1.1.2 Product code**

006 1050

**Registration number**

01-2119463258-33

**1.2 Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Recommended use**

Painting work.

Description: Thinner

**1.3 Details of the supplier of the safety data sheet****1.3.1 Supplier**

Tikkurila Oyj

**P.O.Box**

P.O.Box 53

**Postcode and post office**

FI-01301 VANTAA

FINLAND

**Telephone**

+358 9 857 71

**Telefax**

+358 9 8577 6936

**1.3.4 Responsible for the Safety Data Sheet:**

Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

**1.4 Emergency telephone number****1.4.1 Telephone number, name and address**

Tikkurila Oyj, Environment and Safety: +358 9 857 71

**2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****1272/2008 (CLP)**

Flam. Liq. 3, H226

Asp. Tox. 1, H304

STOT SE 3, H336

Aquatic Chronic 3, H412

EUH066

**67/548/EEC - 1999/45/EC**

Xn; R10-65-66

**2.2 Label elements****1272/2008 (CLP)**

GHS07 - GHS08 - GHS02

Signal word **Danger****Hazard Statements**

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

EUH066

Repeated exposure may cause skin dryness or cracking.

**Precautionary Statements**

P261A

Avoid breathing mist/vapours/spray.

P271

Use only outdoors or in a well-ventilated area.

P301+P310+P331

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

P101

If medical advice is needed, have product container or label at hand.

P405

Store locked up.

P102

Keep out of reach of children.



**WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)**

Date 26.7.2011

Previous date: 3.12.2010

**Contains:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
EC number 919-857-5

**2.3 Other hazards**

Other hazards are not known.

**3. COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substances**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics  
contains benzene less than 0,1 w-%.  
EC number 919-857-5  
See Section 16 for full text of R-phrases and H-statements.

**4. FIRST AID MEASURES****4.1 Description of first aid measures**

In all cases of doubt, or when symptoms persist, seek medical attention.

**4.1.2 Inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Seek medical attention.

**4.1.3 Skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.

**4.1.4 Eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 15 minutes and seek medical advice if necessary.

**4.1.5 Ingestion**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

**4.3 Indication of immediate medical attention and special treatment needed**

Aspiration into the lungs can cause fatal chemical pneumonitis. If nausea or irritation do not appear after ingestion, give 50...100 g medicinal carbon in water slurry.

**5. FIREFIGHTING MEASURES****5.1 Extinguishing media****5.1.1 Suitable extinguishing media**

Recommended: Alcohol resistant foam, CO2, powders or water spray/mist.

**5.1.2 Extinguishing media which must not be used for safety reasons**

Do not use strong water jets.

**5.2 Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

**5.3 Advice for firefighters**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

**6. ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

**WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)**

Date 26.7.2011

Previous date: 3.12.2010

**6.2 Environmental precautions**

Do not allow to enter drains or water courses.

**6.3 Methods and materials for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand or vermiculite and place in a container for disposal according to local regulations. Clean preferably with a detergent; avoid the use of solvents.

**6.4 Reference to other sections**

See also Section 13 for waste disposal instructions.

**7. HANDLING AND STORAGE****7.1 Precautions for safe handling**

Vapours are heavier than air and may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Isolate from sources of heat, sparks and open flame. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. No sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition. No smoking. Keep away from oxidising agents, from strongly alkaline and strongly acid materials. Keep container tightly closed.

**7.3 Specific end use(s)**

None.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

The product does not contain reportable concentrations of substances with the exposure limit values (Occupational Exposure Limit Values according to EU Directives and Threshold Limit Values according to ACGIH 2009).

**8.2 Exposure controls****8.2.1 Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**8.2.2 Individual protection measures****8.2.2.1 Respiratory protection**

Use appropriate certified respirators, with gas and vapour filter A, during sanding with dust filter P2, if ventilation is insufficient. During spray-application use respirators with gas, vapour and dust filter A/P3. During continuous and long-term work the use of motor-driven or air-fed respirators is recommended.

**8.2.2.2 Hand protection**

Always wear protective gloves.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Gloves should be replaced regularly. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended protective glove type is e.g.: nitrile rubber (breakthrough time > 480 min.), laminated foil (breakthrough time > 480 min.)

**8.2.2.3 Eye/face protection**

Use safety eyewear designed to protect against splash of liquids.

**8.2.2.4 Skin protection**

Personnel should wear protective clothing.

When necessary, wear anti-static protective clothing made of natural fibre or of high temperature resistant synthetic fibre.

**WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)**

Date 26.7.2011

Previous date: 3.12.2010

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>9.1</b>	<b>Important Health Safety and Environmental Information</b>	
<b>9.1.1</b>	<b>Appearance</b>	
	Liquid, strong odour	
<b>9.1.6</b>	<b>Initial boiling point and boiling range</b>	150 - 200 °C
<b>9.1.7</b>	<b>Flash point</b>	36 °C
<b>9.1.10</b>	<b>Explosive properties</b>	
<b>9.1.10.1</b>	<b>Lower explosion limit</b>	1,4 vol-%
<b>9.1.10.2</b>	<b>Upper explosion limit</b>	7,6 vol-%
<b>9.1.11</b>	<b>Vapour pressure</b>	1 kPa (38 °C)
<b>9.1.13</b>	<b>Relative density</b>	0,78
<b>9.1.14</b>	<b>Solubility(ies)</b>	
<b>9.1.14.1</b>	<b>Water solubility</b>	poorly soluble (< 50 mg/l, 20 °C)
<b>9.2</b>	<b>Other information</b>	
	None.	

**10. STABILITY AND REACTIVITY**

<b>10.1</b>	<b>Reactivity</b>	
	See section 10.5.	
<b>10.2</b>	<b>Chemical stability</b>	
	Stable under recommended storage and handling conditions (see section 7).	
<b>10.3</b>	<b>Possibility of hazardous reactions</b>	
	See section 10.5.	
<b>10.4</b>	<b>Conditions to avoid</b>	
	In confined or poorly ventilated spaces solvent vapours may form explosive mixtures with air. When exposed to high temperatures may produce hazardous decomposition products.	
<b>10.5</b>	<b>Incompatible materials</b>	
	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.	
<b>10.6</b>	<b>Hazardous decomposition products</b>	
	Hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. may produce when exposed to high temperatures.	

**11. TOXICOLOGICAL INFORMATION**

<b>11.1</b>	<b>Information on toxicological effects</b>	
<b>11.1.7</b>	<b>Aspiration hazard</b>	
	The product contains solvent naphtha, which may cause lung damage if swallowed.	
<b>11.1.8</b>	<b>Other information on acute toxicity</b>	
	<b>Inhalation:</b> Long term exposure to spray mist or solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.	
	<b>Skin contact:</b> Repeated or prolonged contact with the preparation causes removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.	
	<b>Ingestion:</b> Ingestion may cause nausea, diarrhoea and vomiting.	

**12. ECOLOGICAL INFORMATION**

<b>12.1</b>	<b>Toxicity</b>	
-------------	-----------------	--

**WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)**

Date 26.7.2011

Previous date: 3.12.2010

- 12.1.1 Aquatic toxicity**  
LC50 > 100 mg/l; fish, algae, daphnia magna.
- 12.2 Persistence and degradability**
- 12.2.1 Biodegradation**  
Readily biodegradable (estimate).
- 12.3 Bioaccumulative potential**  
Octanol/water partition coefficient log Kow = 2-7.
- 12.4 Mobility in soil**  
No data available.
- 12.5 Results of PBT and vPvB assessment**  
No data available.
- 12.6 Other adverse effects**  
The product should not be allowed to enter drains or water courses.

**13. DISPOSAL CONSIDERATIONS**

- 13.1 Waste treatment methods**
- Product residues:**  
Gather residues into waste containers. Destroy according to the rules given by local authorities. EWC-code for liquid waste is e.g 08 01 11 (waste paint and varnish containing organic solvents or other dangerous substances).
- Packaging waste:**  
Empty cans should be recycled or disposed of in accordance with local regulations.

**14. TRANSPORT INFORMATION**

- 14.1 UN number** 1268
- 14.2 UN proper shipping name** petroleum distillates, n.o.s. (hydrocarbons)
- 14.3 Transport hazard class(es)** 3
- 14.4 Packing group** III
- 14.5 Environmental hazards**  
The product is not classified as environmentally hazardous according to international transport regulations.
- 14.6 Special precautions for users**  
None known.
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
None known.
- 14.8 Further Information**  
EmS: F-E,S-E

**15. REGULATORY INFORMATION**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
None known.
- 15.2 Chemical safety assessment**  
Has not been performed.

**16. OTHER INFORMATION**

- 16.5 Full text of R-phrases and/or Hazard statements (H-statements) referred to under sections 2 and 3**
- |      |   |
|------|---|
| R10  | Flammable.  |
| R65  | Harmful: may cause lung damage if swallowed.          |
| R66  | Repeated exposure may cause skin dryness or cracking. |
| H226 | Flammable liquid and vapour.                          |

**WHITE SPIRIT 1050 with mild odour (LAKKABENSIINI 1050)**

Date 26.7.2011

Previous date: 3.12.2010

---

H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**16.8 Additional information**

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 453/2010 to Regulation (EC) No 1907/2006 (REACH).

The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Additional information available from:

Tikkurila Oyj, Product Safety, P.O. Box 53, FIN-01301 VANTAA, FINLAND,  
Telephone +358 9 857 71, Fax +358 9 8577 6936, E-mail: [productsafety@tikkurila.com](mailto:productsafety@tikkurila.com)

**Signature**

a/ome